

Solis-80K-5G-PRO

Solis Three Phase Grid-Tied Inverters

Efficient

- 6 MPPTs, max. efficiency 98.5%
- > 150% DC/AC ratio
- Compatible with bifacial modules

Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Nighttime PID recovery function (optional)

Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector

Models:

Solis-80K-5G-PRO



DATASHEET

Solis-80K-5G-PRO

Models	80K
Input DC	
Max. input voltage	1100 V
Rated voltage	600 V
Start-up voltage	180 V
MPPT voltage range	160 - 1000 V
Max. input current	3 × (40 A / 32 A)
Max. short circuit current	6 × 50 A
MPPT number / Max. input strings number	6 / 12
Output AC	
Rated output power	80 kW
Max. apparent output power	88 kVA
Max. output power	88 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V
Rated grid frequency	50 Hz / 60 Hz
Rated grid output current	121.6 A / 115.5 A
Max. output current	133.7 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
THDi	< 3%
Efficiency	
Max. efficiency	98.5%
EU efficiency	98.0%
Protection	
DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	DC Type II / AC Type II
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Strings monitoring	Yes
I/V Curve scanning	Yes
Integrated AFCI 2.0	Optional
Integrated PID recovery	Optional
Integrated DC switch	Yes
Integrated AC switch	Optional
General Data	
Dimensions (W × H × D)	1065 × 585 × 363 mm
Weight	78 kg
Topology	Transformerless
Self-consumption (night)	< 2 W
Operating ambient temperature range	-30 ~ +60°C
Relative humidity	0 - 100%
Ingress protection	IP66
Cooling concept	Intelligent fan-cooling
Max. operation altitude	4000 m
Grid connection standard	G99, IEC61727, EN50549-1/2, VDE4110
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4
Features	
DC connection	MC4 connector
AC connection	OT terminal (max. 240 mm ²)
Display	LCD
Communication	RS485, Optional: Wi-Fi, GPRS, PLC